



Roda
Wheel
Roue



Pressão recomendada
Recommended pressure
Pression recommandée



Diâmetro da roda
Wheel diameter
Diamètre de la roue



Velocidade máxima
Maximum speed
Vitesse maximum



Largura da Roda
Wheel width
Largeur de la roue



Jante utilizada
Wheel-rim to use
Jante utilisée



Diâmetro do furo
Hub bore
Diamètre du trou



Capacidade de carga
Load capacity
Capacité de charge



Rolamento de esferas
Balls bearings
Roulement à billes













Número de telas
PR number
Numéro de Plis









RODAS PNEUMÁTICAS PARA ATRELADOS E CARAVANAS

PNEUMATIC WHEELS FOR TRAILERS AND CARAVANS

ROUES PNEUMATIQUES POUR REMORQUES LÉGÈRES ET CARAVANES

|  | |  |  |  |  |  |  |  |  |  |
|---|----------------------|---|---|---|---|---|--|---|---|---|
| Código/Code | Ref. | mm | mm | | | P.R. | bar | km/h | Código Code | kg |
| 10 72 98 | 4.50-10C-4TL/S-RE-25 | 490 | 125 | 25 | 6205 2Z | 4 | 2.0 | 100 | 30 35 04 | 325 |



|  | |  |  |  |  |  |  |  |
|---|-----------------------|---|---|---|---|--|---|---|
| Código/Code | Ref. | mm | mm | P.R. | bar | km/h | Código Code | kg |
| 10 72 06 | 16.5x6.5-8/4TL/S 98x4 | 410 | 160 | 4 | 3.1 | 130 | 30 54 02 | 280 |











RODAS PNEUMÁTICAS PARA ATRELADOS E CARAVANAS









PNEUMATIC WHEELS FOR TRAILERS AND CARAVANS

ROUES PNEUMATIQUES POUR REMORQUES LÉGÈRES ET CARAVANES











| | |  |  |  |  |  |  |  |  |
|-------------|------------------------|---|---|---|--|---|---|---|---|
| Código/Code | Ref. | mm | mm | | | bar | km/h | Código Code | kg |
| 10 72 04 | 4.80/4.00-8/4TL/S 98x4 | 410 | 110 | 4 | | 4.0 | 130 | 30 25 03 | 265 |
| 10 72 13 | 4.50-10C/4TL/S 98x4 | 490 | 125 | 4 | | 3.5 | 130 | 30 35 01 | 325 |
| 10 72 14 | 5.00-10C/4TL/S 98x4 | 510 | 145 | 4 | | 3.5 | 130 | 30 35 01 | 355 |
| 10 72 05 | 145-10/6TL/S 98x4 | 490 | 145 | 6 | | 4.0 | 130 | 30 35 01 | 325 |



| | |  |  |  |  |  |  |  |  |
|-------------|---------------------|--|--|--|---|--|--|--|--|
| Código/Code | Ref. | mm | mm | | | bar | km/h | Código Code | kg |
| 10 72 23 | 145/70 R-13/TL 98x4 | 535 | 145 | - | | 2.5 | 140 | 30 40 19 | 345 |
| 10 72 27 | 155/70 R-13/TL 98x4 | 550 | 160 | - | | 2.5 | 140 | 30 45 24 | 387 |
| 10 72 31 | 165/70 R-13/TL 98x4 | 570 | 170 | - | | 2.5 | 140 | 30 45 24 | 437 |
| 10 72 35 | 175/70 R-13/TL 98x4 | 580 | 180 | - | | 2.5 | 140 | 30 45 24 | 475 |
| 10 73 53 | 185/70 R-13/TL 98x4 | 590 | 189 | - | | 2.5 | 140 | 30 45 24 | 530 |
| 10 72 39 | 185/70 R-14/TL 98x4 | 630 | 200 | - | | 2.5 | 140 | 30 50 15 | 560 |
| 10 73 52 | 175 R-14C/TL-112x5 | 634 | 178 | - | | 4.5 | 140 | 30 50 42 | 775 |
| 10 72 44 | 195 R-14C/8TL-112X5 | 678 | 206 | 8 | | 4.5 | 100 | 30 50 42 | 900 |



| | |  |  |  |  |  |  |  |  |
|-------------|---------------------|---|---|---|--|---|---|---|---|
| Código/Code | Ref. | mm | mm | | | bar | km/h | Código Code | kg |
| 10 72 42 | 195 R-14C/8TL 140x5 | 678 | 206 | 8 | | 4.5 | 140 | 30 50 17 | 750 |



Roda
Wheel
Roue



Pressão recomendada
Recommended pressure
Pression recommandée



Diâmetro da roda
Wheel diameter
Diamètre de la roue



Velocidade máxima
Maximum speed
Vitesse maximum



Largura da Roda
Wheel width
Largeur de la roue



Jante utilizada
Wheel-rim to use
Jante utilisée



Número de telas
PR number
Numéro de Plis











Capacidade de carga
Load capacity
Capacité de charge









RODAS PNEUMÁTICAS PARA ATRELADOS E MÁQUINAS AGRÍCOLAS

PNEUMATICS WHEELS FOR AGRICULTURAL-TRAILERS AND AGRICULTURAL MACHINES

ROUES PNEUMATIQUES POUR REMORQUES AGRICOLES ET MACHINES AGRICOLES

|  | |  |  |  |  |  |  |  |
|---|-------------------|---|---|---|---|--|---|---|
| Código/Code | Ref. | mm | mm | P.R. | bar | km/h | Código Code | kg |
| 10 73 01 | 6,00-16/6TT 205x6 | 736 | 177 | 6 | 2.75 | 40 | 30 45 07 | 690 |
| 10 73 39 | 6,00-16/6TT 140x5 | 736 | 177 | 6 | 2.75 | 40 | 30 45 05 | 690 |



|  | |  |  |  |  |  |  |  |
|---|-----------------------|---|---|---|---|--|---|---|
| Código/Code | Ref. | mm | mm | P.R. | bar | km/h | Código Code | kg |
| 10 72 53 | 10.0/80-12/10TL 140x5 | 730 | 277 | 10 | 3.9 | 40 | 30 70 02 | 1050 |











RODAS PNEUMÁTICAS PARA ATRELADOS E MÁQUINAS AGRÍCOLAS

PNEUMATICS WHEELS FOR AGRICULTURAL-TRAILERS AND AGRICULTURAL MACHINES









ROUES PNEUMATIQUES POUR REMORQUES AGRICOLES ET MACHINES AGRICOLES



|  | |  |  |  |  |  |  |  |
|---|--------------------------|---|---|--|---|---|---|---|
| Código/Code | Ref. | mm | mm | | bar | km/h | Código Code | kg |
| 10 72 57 | 10.0/75-15.3/10TL 140x5 | 779 | 277 | 10 | 3.9 | 40 | 30 90 02 | 1550 |
| 10 72 55 | 10.0/75-15.3/10TL 205x6 | 779 | 277 | 10 | 3.9 | 40 | 30 90 04 | 1550 |
| 10 72 59 | 10.0/75-15.3/12TL 205x6 | 779 | 277 | 12 | 4.7 | 40 | 30 90 04 | 1700 |
| 10 72 69 | 11.5/80-15.3/12TL 205x6 | 868 | 305 | 12 | 4.1 | 40 | 30 90 04 | 2180 |
| 10 72 71 | 11.5/80-15.3/14TL 205x6 | 868 | 305 | 14 | 4.1 | 40 | 30 90 09 | 2430 |
| 10 72 76 | 12.5/80-15.3/14TT 205x6 | 915 | 322 | 14 | 4.3 | 40 | 30 90 17 | 2650 |
| 10 73 41 | 400/60-15.5/14TL 205x6 | 908 | 436 | 14 | 3.6 | 40 | 30 13 03 | 2600 |
| *10 73 47 | 400/60-15.5/14TL 205x6TR | 908 | 436 | 14 | 4.9 | 40 | 30 13 03 | 2600 |

* Piso de tração; *Traction floor*; chaussée de traction











|  | |  |  |  |  |  |  |  |
|---|--------------------------|---|---|---|---|---|---|---|
| Código/Code | Ref. | mm | mm | | bar | km/h | Código Code | kg |
| 10 72 45 | 10.0/75-15.3/14TL 205x6 | 779 | 277 | 14 | 4.7 | 40 | 30 90 14 | 1900 |
| 10 72 46 | 400/60-15.5/14TL 205x6TR | 908 | 436 | 14 | 4.9 | 40 | 30 13 18 | 2725 |

MODELO FLORESTAL / FORESTRY RIM / MODÈLE FORESTIER









RODAS PNEUMÁTICAS COM JANTE DE ARO DESMONTÁVEL PARA ATRELADOS E MÁQUINAS AGRÍCOLAS

PNEUMATIC WHEELS WITH MULTI-PIECE RIMS FOR AGRICULTURAL-TRAILERS AND AGRICULTURAL MACHINES

ROUES PNEUMATIQUES À CERCLE POUR REMORQUES AGRICOLES ET MACHINES AGRICOLES

|  | |  |  |  |  |  |  |  |
|---|----------------------|---|---|---|---|--|---|---|
| Código/Code | Ref. | mm | mm | P.R. | bar | km/h | Código Code | kg |
| 10 73 14 | 9.00-16/14TT/3 205x6 | 898 | 259 | 14 | 7.0 | 40 | 30 65 03 | 1800 |
| 10 73 18 | 9.00-16/14TT/3 205x6 | 898 | 259 | 14 | 7.0 | 40 | 30 65 15 | 1800 |



|  | |  |  |  |  |  |  |  |
|---|-----------------------|---|---|---|---|--|---|---|
| Código/Code | Ref. | mm | mm | P.R. | bar | km/h | Código Code | kg |
| 10 73 26 | 7.00-16/12TT/3D 205x6 | 794 | 210 | 12 | 6.0 | 40 | 30 55 05 | 1250 |
| 10 73 24 | 7.50-16/14TT/3D 205x6 | 814 | 225 | 14 | 7.0 | 40 | 30 55 05 | 1350 |
| 10 73 23 | 7.50-20/12TT/3D 275x8 | 914 | 225 | 12 | 6.75 | 40 | 30 60 05 | 1800 |
| 10 73 28 | 7.50-20/14TT/3D 275x8 | 914 | 225 | 14 | 6.65 | 40 | 30 60 05 | 1850 |
| 10 73 40 | 8.25-20/14TT/3D 205x6 | 980 | 239 | 14 | 6.75 | 40 | 30 60 01 | 1950 |
| 10 73 21 | 8.25-20/14TT/3D 275x8 | 980 | 239 | 14 | 6.75 | 40 | 30 60 05 | 1950 |

